

<b>DESCRIPTION</b>	<p>WIN All-Purposes Spray is based on high quality nitrocellulose and acrylic resin that gives the multi-purposes aerosol product. The properties of this product are fast dry, high gloss and good adhesion on plastic, metal and wood which have been primed with suitable primer.</p>																	
<b>TYPICAL USE</b>	<p>It is most versatile and handy for multi-perposes application such as motorcycle, old table, chair, nursery furniture, toys, shipping marks, steel chairs, bicycles, electric fan, lamp and etc.</p>																	
<b>PHYSICAL PROPERTIES</b>	<p><b>Type</b> : Nitrocellulose and Acrylic Lacquer Resin</p> <p><b>Color</b> : Wide range of colors. Please ask for catalog.</p> <p><b>Gloss Level</b> : Matt, Semi-gloss and Gloss</p> <p><b>Pressure</b> : 4 Bar</p> <p><b>Flash Point</b> : -10 °C</p> <p><b>Coverage(by theory)</b> : 1.40 sq.meter / coat / can</p> <p>Remark – Actual surface coverage is depend on application condition, experience, technique, shape and dimension of the object that need to spray on.</p> <table border="1"> <tr> <td rowspan="2"><b>Drying Time</b></td> <td>Temperature</td> <td>25°C</td> <td>30°C</td> </tr> <tr> <td>Surface dry</td> <td>15 – 20 minutes</td> <td>10 – 15 minutes</td> </tr> <tr> <td></td> <td>Hard dry</td> <td>60 – 70 minutes</td> <td>45 – 60 minutes</td> </tr> <tr> <td rowspan="2"><b>Recoatible Time</b></td> <td>Minimum</td> <td>10 - 15 minutes</td> <td>8 – 10 minutes</td> </tr> </table>			<b>Drying Time</b>	Temperature	25°C	30°C	Surface dry	15 – 20 minutes	10 – 15 minutes		Hard dry	60 – 70 minutes	45 – 60 minutes	<b>Recoatible Time</b>	Minimum	10 - 15 minutes	8 – 10 minutes
<b>Drying Time</b>	Temperature	25°C	30°C															
	Surface dry	15 – 20 minutes	10 – 15 minutes															
	Hard dry	60 – 70 minutes	45 – 60 minutes															
<b>Recoatible Time</b>	Minimum	10 - 15 minutes	8 – 10 minutes															
	<b>APPLICATION INFORMATION</b>	<p><b>Surface Preparation</b> : The surface must be clean and free of dirt, grease, oil, wax, salt, old paint and other contaminants. : Chalky surfaces or loose material must be removed by stiff brush. : The surface must be clean with suitable cleansing solution and water then rinse thoroughly with fresh water and allow to fully dry.</p> <p><b>Primer</b> : Apply suitable primer for desired surface or apply with WIN Primer Surfacer Grey Spray #266 at least 2 coats to enhance adhesion.</p> <p><b>Topcoat</b> <ol style="list-style-type: none"> <li>1. Before use, shake the can of <b>WIN All-Purposes Spray</b> thoroughly around 2 minutes and shake periodically during spray.</li> <li>2. Spray with distance from the required object around 20 – 25 cm and spray from left to right and top to bottom of the object.(Depend on skill and experience)</li> <li>3. The first coat must be thin and allow to dry at least 10 minutes before spray the second coat.</li> </ol> </p> <p><b>Application Method</b> : Spray</p> <p><b>Condition During Application</b> : Use respiratory mask with charcoal and dust filter. For prolonged or repeated handling, use nitrile gloves or polyvinyl alcohol gloves. Use safety eye wear designed to protect against splash of liquids. : No smoking.</p>																
<b>STORAGE</b>	<p>: The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition.</p> <p>: After used, the container must be kept tightly closed.</p>																	
<b>SHELF LIFE</b>	<p>: 36 months at 25 – 30°C (from manufacturing date)</p>																	

**PACKAGE**

: 400 cc / Can

**HEALTH AND SAFETY**

: Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. In case of eye contact, immediately flush the eye with plenty of water at least 15 minutes and get medical attention.

: For more informations on health, safety, hazards and precautions for use of this product, please ask for Material Safety Data Sheet.

**DISCLAIMER**

: The informations in this Technical Data Sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice.

<p><b>คุณลักษณะ:</b></p>	<p>สเปรย์ วิน ผลิตจากโพลีเอสเตอร์และอะคริลิกเรซินคุณภาพสูง เป็นสเปรย์อเนกประสงค์ ที่มีคุณสมบัติแห้งไว ให้ความเงาสูง และมีการยึดเกาะที่ดี ทั้งบนพื้นผิวพลาสติก โลหะและไม้ โดยใช้สีรองพื้นที่เหมาะสม</p>												
<p><b>การใช้งาน</b></p>	<p>ใช้งานง่าย สะดวก และใช้งานได้บนอเนกประสงค์ ไม่ว่าจะเป็นจักรยานยนต์ โต๊ะ เก้าอี้ ของเด็กเล่น เครื่องหมายสำหรับขนส่ง จักรยาน พัดลม โคมไฟ ฯลฯ</p>												
<p><b>ข้อมูลทางเทคนิค</b></p> <p>ประเภทของสี</p> <p>สี</p> <p>ระดับความเงา</p> <p>ความดัน</p> <p>จุดควบไฟ</p> <p>การปกคลุมพื้นผิว (โดยทฤษฎี)</p> <p>ระยะเวลาแห้ง</p> <p>ระยะเวลาแห้งก่อนพ่นกับ</p>	<p>โพลีเอสเตอร์และ อะคริลิก แล็กเกอร์ เรซิน</p> <p>เลือกเม็ดสีได้จากแคตตาล็อก</p> <p>แบบด้าน แบบกึ่งเงา แบบเงา</p> <p>4 บาร์</p> <p>-10 °C</p> <p>1.40 ตารางเมตร ต่อ เทียว ต่อ กระป๋อง</p> <p>หมายเหตุ : ค่าการปกคลุมพื้นผิวขึ้นกับสภาวะระหว่างใช้งาน ประสบการณ์ เทคนิคการพ่น รวมถึงรูปร่างและขนาดกว้าง-ยาว ของวัตถุที่นำมาพ่น</p> <table border="1" data-bbox="526 996 1037 1164"> <thead> <tr> <th>อุณหภูมิ</th> <th>25°C</th> <th>30°C</th> </tr> </thead> <tbody> <tr> <td>แห้งผิว</td> <td>15 – 20 นาที</td> <td>10 – 15 นาที</td> </tr> <tr> <td>แห้งแข็ง</td> <td>60 – 70 นาที</td> <td>45 – 60 นาที</td> </tr> <tr> <td>อย่างน้อย</td> <td>10 – 15 นาที</td> <td>8 – 10 นาที</td> </tr> </tbody> </table>	อุณหภูมิ	25°C	30°C	แห้งผิว	15 – 20 นาที	10 – 15 นาที	แห้งแข็ง	60 – 70 นาที	45 – 60 นาที	อย่างน้อย	10 – 15 นาที	8 – 10 นาที
อุณหภูมิ	25°C	30°C											
แห้งผิว	15 – 20 นาที	10 – 15 นาที											
แห้งแข็ง	60 – 70 นาที	45 – 60 นาที											
อย่างน้อย	10 – 15 นาที	8 – 10 นาที											
<p><b>ระบบการใช้งาน</b></p> <p>การเตรียมพื้นผิว</p> <p>การรองพื้น</p> <p>การพ่นสีกับหน้า</p> <p>วิธีใช้งาน</p> <p>ข้อแนะนำเวลาปฏิบัติงาน</p>	<p>: พื้นผิวที่จะใช้งานต้องสะอาด ปราศจากฝุ่น, คราบไขมัน, แวกซ์, คราบเกลือ, สีเก่า และสิ่งปนเปื้อนต่างๆ</p> <p>: พื้นผิวที่เป็นขอสลัค หรือ เสื่อมสภาพ ต้องขัดทำความสะอาดด้วยแปรงไนลอน</p> <p>: ทำความสะอาดพื้นผิวด้วยน้ำและน้ำยาทำความสะอาดที่เหมาะสม แล้วล้างด้วยน้ำสะอาดอีกครั้ง ก่อนทาสีให้แห้งสนิท</p> <p>: พ่นสีรองพื้นที่เหมาะสมตามชนิดของวัสดุหรือพื้นผิวที่ต้องการ จำนวน 2 เทียว หรือ พ่นด้วยสเปรย์รองพื้นเทา วิน เบอร์ 266 จำนวน 2 เทียว เพื่อเพิ่มการยึดเกาะ</p> <p>1. ก่อนใช้งานควรระวังการป้องกัน <b>สเปรย์อเนกประสงค์ วิน</b> ประมาณ 2 นาที จนเสียงลูกแก้วดังสม่ำเสมอ และอย่าเป็นระยะระหว่างพ่น</p> <p>2. พ่นห่างจากชิ้นงานประมาณ 20 – 25 เซนติเมตร โดยพ่นจากซ้ายไปขวา และ จากบนลงล่าง (ขึ้นกับความถนัดและประสบการณ์)</p> <p>3. เทียวแรกควรพ่นบางๆ แล้วทิ้งให้แห้งอย่างน้อย 10 นาที ก่อนพ่นทับเทียวที่ 2</p> <p>: การพ่น</p> <p>: ควรสวมอุปกรณ์ป้องกันภัยส่วนบุคคล เช่น แว่นตา ถุงมือ และ ฝาปิดจมูก</p> <p>: ห้ามสูบบุหรี่ระหว่างการใช้งาน</p>												
<p><b>การเก็บรักษา</b></p>	<p>: สินค้าจำเป็นต้องเก็บรักษาตามข้อกำหนด ควรเก็บในที่แห้ง มีอากาศถ่ายเทดี ไม่ควรเก็บในบริเวณที่รับแสงแดดโดยตรง ต้องเก็บให้พ้นจากแหล่งกำเนิดความร้อนและประกายไฟ</p> <p>: หลังใช้งาน ควรปิดฝาให้สนิท</p>												
<p><b>อายุผลิตภัณฑ์</b></p>	<p>: 36 เดือน ที่อุณหภูมิ 25 – 30°C (นับจากวันที่ผลิต)</p>												

ขนาดบรรจุ	: 400 ซีซี ต่อ กระป๋อง
ข้อมูลสุขภาพและความปลอดภัย	<p>: กรุณาดูข้อควรระวังที่ติดไว้หน้ากระป๋อง การทำงานสีควรทำในที่ที่อากาศถ่ายเทสะดวก อย่าสูดหายใจละอองของสี ควรใส่หน้ากากเมื่อทำการพ่นสีและพยายามเลี่ยงมิให้สัมผัสผิวหนัง ถ้าสีหกใส่ผิวหนังควรล้างด้วยน้ำสะอาดกับสบู่ทันที ถ้าถูกตาควรล้างด้วยน้ำสะอาดทันทีและ รีบไปพบแพทย์</p> <p>: รายละเอียดด้านความปลอดภัยเกี่ยวกับการใช้ผลิตภัณฑ์ สี-บุไว้ไว้ในข้อมูลด้านความปลอดภัย</p>
การสงวนสิทธิ์เรียกร้อง	<p>: รายละเอียดด้านความปลอดภัยเกี่ยวกับการใช้ผลิตภัณฑ์ สี-บุไว้ไว้ในข้อมูลด้านความปลอดภัย</p> <p>: รายละเอียดข้างบนนี้ได้มาโดยการทดลอง และจากประสบการณ์ที่ผ่านมา เนื่องจากสีถูกนำไปใช้ในภาวะแตกต่างกันเราจึงไม่สามารถรับประกันในสิ่งอื่นใดนอกจากคุณภาพของสีเท่านั้น บริษัทของสงวนสิทธิ์ที่จะเปลี่ยนแปลงข้อมูลโดยมิต้องแจ้งล่วงหน้า</p>